

WX200

WX200 is an expandable, abrasion resistant, highly flame retardant braided sleeve used on cable assemblies, wire harnesses and hoses. It is made from Halar®(E-CTFE) fluoropolymer monofilaments that are highly resistant to most solvents and hydrocarbons, such as jet fuels, gasoline, diesel fuels, hydraulic fluids and cleaning fluids. Halar® is low outgassing and will not support combustion in air. WX200 is an excellent choice anywhere that high temperature, extreme flammability and excellent chemical resistance are essential.

Specifications:

U.L. (VW-1) & C.S.A. (FR-1) rated
 Operating Temperature: -100°F (-75°C) to +302°F (150°C)
 Monofilament Diameter: 0.011" (nom.)
 Wall Thickness: 0.025" (nom.)

Standard colors: (B) Black w/ one white tracer
 (W) White w/ one black tracer
 (2) Red w/white tracer

Part number makeup: **WX200** - **3/8** - **B**
 | | |
 Material Size Color

Size (inches)	Size Range (inches)	Weight lb./1000ft	Standard Spool Qty.
1/8	3/32 - 1/4	2.50	1000 ft.
1/4	1/8 - 3/8	3.70	1000 ft.
3/8	3/16 - 5/8	8.60	500 ft.
1/2	1/4 - 3/4	11.40	500 ft.
3/4	1/2 - 1-1/4	17.20	500 ft.
1.25	3/4 - 1-1/2	26.00	250 ft.
1.75	1-1/4 - 2-3/4	40.00	250 ft.
2	1-1/2 - 3	46.00	100 ft.
2.50	1-3/4 - 4	50.00	100 ft.

Halar® is a registered trademark of the Allied Chemical Corporation.