



SumiMark[®] SM3 Black and Super Ribbon Comparison

Product Overview:

SumiMark[®] SM3 Black and Super Ribbon thermal transfer ribbons have been chosen and tested specifically with the SumiMark[®] line of thermal transfer printers to provide optimal print quality and adherence. Although both products meet commonly recognized industry standards, there are some applications whereby SM3 Super Ribbon is recommended, as noted in table below.

	Meets SAE-AS5942 MIL-STD-202 Method 215J	Visual Print Quality	Solvent and Abrasion Resistance Mark Permanence	Suggested SumiMark SM3 Product Use
SM3 Black	YES	GOOD	GOOD	All SM3 Products except SM3-60 and SM-CM
SM3 Super Ribbon	YES	GOOD	BETTER	SM3-60 and SM-CM

Storage Conditions:

- Temperature: 5°C to 35°C
- Humidity: 10% to 85% Relative Humidity
- Light: Avoid direct sunlight

Product Features:

- RoHS and REACH compliant.
- Compatible with all SumiMark[®] III and IV models.
- Supplied in 2" and 3.25" widths.
- Available in Black only.

SUMITOMO ELECTRIC INTERCONNECT PRODUCTS, INC.

	T: 800.758.3515	
915 Armorlite Drive	F: 800.758.3517	
San Marcos, CA 92069-1440	E: customerservice@seipusa.com	
	W: www.seipusa.com	

©2014 Sumitomo Electric Interconnect Products, Inc. All rights reserved. The Sumitomo Electric logo is a registered trademark of Sumitomo Electric Industries. Other products and brand names may be trademarks of their respective owners. The information on this datasheet is believed to be correct a the time of publishing. Specifications given in this publication are subject to change without notice.