

| REVISIONS | | | |
|-----------|-------------|------------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| A | RELEASE | 12/08/2014 | J. LEE |

DESCRIPTION: 22 AWG 3 CONDUCTOR TINNED COPPER, SHIELDED, PVC JACKET

CONDUCTOR SIZE: 22 AWG (7/30)
 CONDUCTOR MATERIAL: TINNED COPPER, ANNEALED, CLASS B
 INSULATION: POLYPROPYLENE
 INSULATION WALL THICKNESS: 0.008 INCHES NOMINAL
 CONDUCTOR COLORS: BLACK, RED, WHITE

CONDUCTOR COUNT: 3 CONDUCTORS
 CABLE LAY: LHL

SHIELD: ALUMINUM MYLAR TAPE, 100% COVERAGE


DRAIN WIRE SIZE: 22 AWG - 19 STRAND
 DRAIN WIRE MATERIAL: TINNED COPPER

JACKET MATERIAL: PVC (POLYVINYL CHLORIDE)
 JACKET WALL THICKNESS: 0.023 INCHES NOMINAL
 JACKET COLOR: BROWN

CABLE DIAMETER: 0.144 INCHES NOMINAL +/- 0.018 (3.65 MM +/- 0.45 MM)

WEIGHT: 17 LBS PER 1,000 FEET

RATINGS:
 VOLTAGE: 300 V RMS
 UL LISTED AS TYPE CM C(UL)US 75°C PER UL STANDARD 444 AND AS TYPE CL3 PER UL STANDARD 13
 ALL MATERIALS USED IN THE MANUFACTURE OF THIS CABLE ARE ROHS AND REACH COMPLIANT
 CABLE IS UL APPROVED FOR SUNLIGHT RESISITANT APPLICATIONS
 COUNTRY OF ORIGIN: UNITED STATES

| ITEM NO. | QTY REQ'D | PART NUMBER | DESCRIPTION | | | | |
|---|-----------|-------------|-------------|--|-----------|-------------|--------------|
| DO NO SCALE THIS DRAWING | | DRAWN BY | DATE |  www.silverstatewire.com | | | |
| ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCE: ANGLES ± 0.5° DEC. .XX ± 0.03 DEC. .XXX ± 0.010 | | D. MILLER | 12/08/2014 | | | | |
| | | CHECKED BY | DATE | | | | |
| | | J. LEE | 12/08/2014 | | | | |
| THIS DRAWING IS THE PROPERTY OF SILVER STATE WIRE & CABLE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF THIS DESIGN WITHOUT THE WRITTEN PERMISSION OF SILVER STATE WIRE AND CABLE. | | APPROVED BY | DATE | DESCRIPTION | | | |
| | | J. LEE | 12/08/2014 | 22 AWG, 3 COND, SHLD, CABLE | | | |
| | | APPROVED BY | DATE | SIZE | CAGE CODE | DWG NO. | REV |
| | | N/A | N/A | A | 01CV1 | S-4367-0011 | A |
| | | | | SCALE | NONE | WT | SHEET 1 OF 1 |