



SUMIMARK™ IV PLUS Marking System

Applications:

- Wire identification

Product Features:

- Integrated cutter for full or partial cutting to length
- Prints on material diameters from 1/16" to 2"
- Prints on 2:1, 3:1 and 4:1 shrink ratios and adhesive lined tubing
- Marks on all colors, including clear
- Full networking capabilities

Required Ribbon & Software:

Software - Sumilabel™

Ribbon - Sumimark™ SM3

Print Performance:

Adherence: SAE-AS5942

MIL-STD-202G, Method 215

Print Specifications:

Print Resolution - 300 DPI

Print Speed - Up to 12 IPS

Print Width - 4" maximum

Print Length - 450" maximum

Description and Part Number:

Sumimark™ IV PLUS

191-78700



FLEXIBLE APPLICATION
COST EFFECTIVE
EASY TO USE

Product Overview

Quality Counts! The Sumimark™ IV PLUS thermal transfer printer is the only on the market designed specifically for marking and cutting Sumimark™ and Sumitag™ heat shrink tubing. The Sumimark IV™ PLUS is manufactured for industrial applications requiring maximum flexibility of applications, ease of use, print quality and reliability.

Lower Cost! Due to optimized design for use with continuous tubing, the Sumimark™ IV PLUS significantly lowers total installed cost vs. formatted tubing.

How can we help? Contact us for more information:

775-356-8969

sales@silverstatewire.com

SUMIMARK™ IV PLUS Marking System

Consumable Parts

Ribbons:

- Sumimark™ SM3, Black 2" (176-20013)
 - Sumimark™ SM3, Black 3.25" (176-20001)
 - Sumimark™ SM3, White 2" (176-20017)
 - Sumimark™ SM3, White 3.25" (176-20016)
 - Sumimark™ SM3 Super Ribbon, Black 1.5" (176-2002)
 - Sumimark™ SM3 Super Ribbon, Black 2" (176-20021)
 - Sumimark™ SM3 Super Ribbon, Black 3.25" (176-20010)
- Colors - available upon request, with MOQ

Cutter Blades and Block:

- SM3&4 Cutter Blade - No Notch. For full cuts. (191-10025)
- SM3&4 Cutter Blade - Triple Notch. Perf cuts. (191-10041)
- SM3&4 Cutting Block - (191-10037)

Other:

- Platen - SM4 PLUS Platen. (191-20002)
- Print Head - SM4 PLUS Print Head 300DPI. (191-70001)

Electrical

- Input - AC 100-240V, 4-2A, 50-60Hz
- LCD Display
- Multi-Function Push Button Controls

Connectivity Interface

- Ethernet
- USB Host - 2 Ports
- RS-232

Sensors

- Gap transmissive
- Black mark reflective
- Ribbon end
- Head open
- Media near end

Physical Dimensions

- Exterior - 10.9" W x 19.8"D x 12.8"H
- Weight - 37lbs

We can help: 775-356-8969

sales@silverstatewire.com