REVISIONS				
REV	DESCRIPTION	DATE	APPROVED	
В	RELEASE	08/04/2022	J. LEE	

Description: 20 AWG 3 Conductor Cable

Conductor

AWG Size & Stranding: 20 AWG, 19x32 Strands, Class C

Material: Annealed Tinned Copper Conductor Count: 3 Conductors

Insulation Material: PVC - Polyvinylchloride

Insulation Wall Thickness: 0.015 Insulation Diameter: 0.0645" ± 0.002" Insulation Color Code: Black, Red, Yellow

Nominal Lay Length: 2.00" LHL (6.0 tw/ft)

Shielded: None Drain Wire: None Binder: None

Jacket Material: PVC - Polyvinylchloride

Jacket Wall thickness: 0.032" Jacket Diameter: 0.208" ± 0.010"

Jacket Color: Black Jacket Ripcord: No

Jacket Weight: 29 Lbs / Mft

Jacket Markings: Cable permanently identified via surface ink-jet print

Print Legend: SILVER STATE WIRE & CABLE J-4862-00252 EXXXXXX 20AWG 3C AU AWM 2517 300V 105°C "ROHS COMPLIANT"

Footage Markers: No

Standards:

UL recognized component as type AWM 2517 per UL standard 758

Insulated conductors are UL recognized component as type AWM 1731 per UL standard 758

Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive

Cable is REACH compliant per Regulation (EC) No 1907/2006 (219) Updated January 15, 2021

Operating Voltage: 300V RMS

Made in the USA

WARNING: This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov . Wash hands after handling

ITEM NO. QTY REQ'D PART NU	MBER	DES					SCRIPTION				
DO NO SCALE THIS DRAWING ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	DRAWN BY D. MILI	LER	DATE 01/07/2021	55WC					3		
TOLERANCE: ANGLES ± 0.5* DEC. JXX ± 0.03 DEC. JXX ± 0.010	J. LEE 01/07/2021 DESC			SILVER STATE WIRE & CABLE www.slverstatewire.com							
THIS DRAWING IS THE PROPERTY OF SILVER STATE WIRE & CABLE AND SHALL NOT BE REPRODUCED, COPIED, OR USED	J. LEE		DATE 01/07/2021	20 AWG, 3 COND, CABLE				REV			
AS THE BASIS FOR THE MANUFACTURE OR SELL OF THIS DESIGN WITHOUT THE WRITTEN PERSMISSION OF SILVER STATE WIRE AND CABLE	APPROVED BY		DATE N/A	A	01C\		J-4862-0	0252 SHEET 1	В		

5

D

В